

Entry Level HMI

GT23
PRODUCT FLYFR





The Mitsubishi Electric GT23 Series of graphic operator terminals are full of outstanding features you wouldn't expect to find in an entry level screen. Simple and sleek design concept with long life cycle components, GT23 Series provide TFT LCD display with 65K colours, VGA resolution and 9 MB of internal memory. All GT23 models can be programmed with GT Works 3 engineering software, which allows users to configure and build modern applications with simple configuration.




65K Colour TFT LCD Display

65K colour TFT LCD display with VGA resolution available in the following screen sizes: 8.4" and 10.4".



In-built Communications

Communication interfaces such as Ethernet, RS-422/485, RS-232, USB host/device and SD memory card are standard features.



Advanced Functionality

Advanced features such as data logging, multi-channel communication and FA transparent function are supported.

Features

- » GT Works3 user-friendly programming software
- » FTP server/client
- » Operation log
- » Data logging
- » Multi-channel

- » Transparent function
- » Operator authentication
- » Backup/restore
- » MELSEC-FX list editor
- » System alarm function
- » GOT screen templates

SPECIFICATIONS

| Specifications | | GT2308-VTBA | GT2308-VTBD | GT2310-VTBA | GT2310-VTBD |
|-------------------------------------|--------------------|--|-------------|--------------------------------|-------------|
| Display unit | Туре | 8.4", TFT, LCD, 65536 colours | | 10.4", TFT, LCD, 65536 colours | |
| | Resolution (pixel) | 640 x 480 | | | |
| Power supply | | 100 - 240 V AC | 24 V DC | 100 - 240 V AC | 24 V DC |
| Memory capacity | (ROM) | 9 MB | | | |
| | (RAM) | 9 MB | | | |
| Memory card | | 1 (SD memory card) | | | |
| Keyboard type | | Touch-panel | | | |
| Function keys | | Touch keys | | | |
| LED indicators | | 1 (power) | | | |
| Interfaces | | Ethernet (TPC/IP), RS232, RS422/485, USB, SD card slot | | | |
| Real-time clock | | Intergrated | | | |
| Network communication possibilities | | Ethernet (TCP/IP), RS232, RS422/485 | | | |
| IP rating (front) | | IP67* | | | |
| Dimensions (WxHxD) mm | | 241 x 194 x 56 | | 303 x 218 x 56 | |
| Weight kg | | 1.5 | | 1.9 | |

Notes:

*The unit may not be used in certain environments where it is subjected to splashing oil or chemicals for a long period of time or soaked in oil mist. Accessories: Programming software GT Works3, cables and interface adapters.

Catalogue

https://bit.ly/GOT-Series

e-Learning

https://www.mitsubishielectric.com/fa/assist/e-learning/eng.html



For further information contact

Email: iasw@meaust.meap.com Website: MitsubishiElectric.com.au